

Flexible AC Current Probe

Model PRO~flex ACP 10000_1

P/N: P-02.800.0 ACP 10000_1/48
P/N: P-02.800.1 ACP 10000_1/36



The new PRO~flex ACP 10000_1 is an AC current Probe utilising the Rogowski principle. It can be used to measure currents up to 10000 Amps from very low frequencies to 10kHz. The flexible and lightweight measuring head allows quick and easy installation in hard to reach areas and with large conductors.

IP 65 **CE**

Electrical Characteristics

Current Ranges (selectable via rotary switch).....	: 100A / 1000A / 10000A AC _{RMS}
Output Sensitivity (AC coupled).....	: 10mV / 1mV / 0.1mV per A
Accuracy (at 25°C).....	: ± 1% of range (45-65Hz)
Load Impedance.....	: 100kΩ minimum
Linearity (10% to 100% of range)	: ± 0.2% of reading
Noise.....	: 80mA (100A) / 400mA (1000A / 10000A range)
Bandwidth (-3dB).....	: 10Hz to 10kHz
Phase Error (45 – 65Hz).....	: ± <1°
Temperature Coefficient.....	: ± 0.08% of reading / °C
Position Sensitivity	: ± 2% of reading
External Field (with cable > 100mm from the head).....	: ± 0.25% of range
Power Supply	: 2 x AA MN 1500 LR6 Alkaline
.....	: 2000 hours, low battery indicator
.....	: external power supply (3V / 100mA)
Overload Indication	: Red LED ON indicates the range overload
Working Voltage (see Safety Standards section).....	: 1000V AC _{RMS} or DC (Probe and Integrator)
.....	: 30V max (Output)

General Characteristics

Probe and Cable Material.....	: Alcryn 2070 NC, LATENE 7H2W V0
Probe Cable Length / Conductor Diameter.....	: 915mm (36") / 291mm (11.4")
.....	: 1220mm (48") / 388mm (15.2")
Probe Cable Diameter.....	: 9.9mm (nominal)
Cable Length (Probe to Integrator box)	: 2m
Output	: 0.5m long lead terminated with
.....	: a safety male BNC
Operating Temperature Range.....	: -20 to +80°C
Storage Temperature Range.....	: -40 to +90°C
Operating Humidity.....	: 15% to 85% (non condensing)
Degree of protection.....	: IP65 Probe, IP40 Integrator module
Colour	: RAL 120 70 75 Lemon green,

ROHS and WEEE Compliant

Safety Standards

EN 61010-1
EN 61010-2-032

1000 V_{RMS}, Category III, 600 V_{RMS}, Category IV, Pollution Degree 2 (Probe and Integrator)

Use of the probe on uninsulated conductors is limited to 1000 V AC_{RMS} or DC and frequencies below 1 kHz.

EMC Standards

EN 61326-2-2

Dimensions (in mm)

