

MICRO ~ flex FLEXIBLE AC Current Probes ACP 1000 SERIES

Accurate, Thin and Flexible

- Three selectable current ranges 10/100/1000A
- 3 Standard conductor diameters 50/70/100mm
- Easy to insert probe in confined spaces
- Multimeter and Oscilloscope versions
- Wide dynamic range 100mA to 1000A AC_{RMS}
- 1000V, CAT III, Pollution degree 2
- Excellent response to rapid current changes
- External power supply option (ACP 1005 only)
- Compact lightweight design
- No magnetic hysteresis, saturation or non linearity



High Accuracy and Wide Dynamic Range

Advanced coupling design results in minimal effect of external magnetic fields and off-centre conductor positioning on probe accuracy.

EN 61010-2-032:2002 and EMC Conformance

Safety features provide the user with confidence when making measurements in hazardous voltage areas. Conformance to EMC standards ensures high reliability through reduced susceptibility to electromagnetic interference.

TYPICAL APPLICATIONS

- Connection to most measuring instruments including multimeters, oscilloscopes or recording devices
- Development and servicing of power electronic equipment
- Analysis of complex current
- Analysis of harmonics, power measurements, measurement of peak loads in mains and in UPS.

ACP 1000_MICROflex RANGE_120731_03

GMC-I PROSyS Ltd.

Allied Business Centre | 1 Potter Place | Skelmersdale | Lancashire | WN8 9PH | United Kingdom
Telephone: +44 (0) 1695 567280 | Fax: +44 (0) 1695 567299
www.i-prosys.com | sales@i-prosys.com

Registered Company Number: 5116760
Vat Number: GB863880193

SPECIFICATIONS

NON-INVASIVE AC CURRENT MEASUREMENT

MODEL	ACP 1000	ACP 1005
Current Ranges (RMS)	10 / 100 / 1000A	
Output Sensitivity	100mV / 10mV / 1mV / A	
Noise (AC rms)	0.1A (10A/100A range), 1A (1000A range)	
Linearity	± 0.2% of reading	
Basic Accuracy	± 1% of reading ± 0.1A (10/100A) / ± 1A (1000A range)	
Conductor position sensitivity	± 2.5% of reading	
Frequency Range (-2dB)	20Hz to 20kHz	20Hz to 100kHz
Phase shift (45 – 65Hz)	<1 degree	
Load Impedance	> 100 kOhms	
Output connection	0.5m lead terminated with 4mm safety plugs	0.5m coax terminated with safety male BNC connector

ENVIRONMENTAL DATA

Operating Temperature -20°C to +65°C (-4°F to 149°F)

Temperature Coefficient ± 0.15% of reading per °C
(± 0.1% of reading per °F)

Storage Temperature
(without battery) -40°C to +75°C (-40°F to 167°F)

POWER SUPPLY

Battery type 2 x AA MN 1500 LR6
 Alkaline

Battery life 1000 hrs ACP 1000
 150 hrs (ACP 1005)

External Power Supply 3V / 100mA (ACP 1005 only)

MECHANICAL DATA

Dimensions (mm) 110 (H) x 65 (W) x 23 (D)

Probe cable diameter 6mm

Cable length 2m (Probe to Integrator)

Probe Conductor
Diameters 50mm (2"), 70mm (3") and
 100mm (4")

GMC-I PROSyS Ltd. offer a wide range of non-invasive Probes and Clamp Meters for the measurement and analysis of Current and Voltage

SAFETY

EN61010-2-032:2002,
EN 61010-031:2002
EN 61010-1:2001
1000V, Measurement Category III, Pollution Degree 2.

EMC Standard EN 61326-2-2:2006

MAXIMUM SAFE VOLTAGES

1000V AC RMS or DC
30V maximum between output and earth

All accuracies stated at 23°C ± 1°C (73.4°F ± 1.8°F)

DEGREE OF PROTECTION

IP50 PROBE	IP40 Integrator
Part No's	MODEL
P-06.600.6	ACP 1000/2
P-06.600.7	ACP 1000/3
P-06.600.8	ACP 1000/4
P-06.600.9	ACP 1005/2
P-06.601.0	ACP 1005/3
P-06.601.1	ACP 1005/4

ACP 1000_MICROflex RANGE_120731_03

GMC-I PROSyS Ltd.

Allied Business Centre | 1 Potter Place | Skelmersdale | Lancashire | WN8 9PH | United Kingdom
Telephone: +44 (0) 1695 567280 | Fax: +44 (0) 1695 567299
www.i-prosys.com | sales@i-prosys.com

Registered Company Number: 5116760
Vat Number: GB863880193